

ALDEBARAN® HI-LINE LED 150 W

Aldebaran HI-LINE



Article No.: **1410000830**

5,4

KG

IP65

IP CODE

20.700

REAL-LUMEN

Description

The HI-LINE LED SERIES is a new LED-based lighting the hall their optimum of use up to a height of approximately 8 meters place. Excellent light output combined with low power consumption underscore the simple recipe which was the basis for the design of this light: Simple elegance combined with excellent performance and an efficiency level that can be seen. The result of these ingredients make the products of HI-LINE LED SERIES is. So much light as necessary and as much light output as possible. As an alternative to the usual hall deep emitters occupy significantly more space, the HI-LINE LED SERIES produces a much more homogeneous light through their specially calculated radiation.

Product Highlights

- Dimmable 1-10 V
- Glare-free thanks to specially frosted lenses
- Robust and insensitive aluminum housing
- No need to change the bulbs

Technical Specifications

General Data

Attribute	Value	Unit
Brand	ALDEBARAN®	
Series	HI-LINE	
Model	LED 150 W	
Temperature (min)	-30	°C
Temperature (max)	+50	°C
Dimensions	1205 x 135 x 110	mm
Weight	5,4	kg
Front Window	Polycarbonat (milky)	
IP Class	IP65	

Lighting Data

Attribute	Value	Unit
Luminant	SMD LED 2835	
Luminous Flux (real)	20700	lm
Colour Temperature	5000	K
CRI	>80	
Durability	50000	h

Electrical Data

Attribute	Value	Unit
Input Voltage	100-240	V
Mains Frequency	50/60	Hz
Type of Current	AC	
Power Consumption	150	W
Protection Class	I	

Accessories

Other

Article No.	Image	Name
1410920045		Nylon strap (2 pcs.) bk, uni. adjustable, 1,75m
1410926024		Hanging set for HI-LINE-lights

Additional Product Images



Subject to technical changes, price adjustments and errors.

Setolite Lichttechnik GmbH Bockhackerstr. 13 42499 Hückeswagen Germany	Tel./Fax +49 2192 / 93624-0 +49 2192 / 93624-25	Web/Email www.setolite.com info@setolite.de
--	--	--

