



ALDEBARAN® GLADIUS 2K LED, 230 V, 160 W, yellow-black

Aldebaran Gladius

Article No.: 1410001311

7,17

KG

IP65

IP CODE

28.000

LUMEN

25.900

REAL-LUMEN

Description

Efficient tools in rescue technology are more important than ever.

The low weight of ALDEBARAN® GLADIUS 2K LED, its compact size and practicality in use were of the same name Short sword to the Romans estimated virtues.

The SETO XPECT®2 LED lens system used in the ALDEBARAN® GLADIUS 2K LED enables a long range for search operations and comprehensive illumination of the close-range area at the same time with virtually no light spill.

A natural color reproduction and reflection even in adverse weather conditions will be achieved through the use of the integrated SETO LifeView Systems, are combined additively in which different colors of light.

The ALDEBARAN® GLADIUS 2K LED has an integrated cable storage for the 10 meter long connection cable, and an integrated handle and a bolt receiving DIN at the bottom. Thus, the ALDEBARAN® GLADIUS 2K LED universal lighting tool and an efficient replacement for traditional halogen lamps.

Product Highlights

- Glare-free SETO XPECT®2-LED lens optics (significantly reduces scattering losses and glare)
- Integrated DIN bolt receiver, cable winder and handle
- SETO LifeView color mixer system for optimal penetration in all weather conditions

Technical Specifications

General Data

Attribute	Value	Unit
Brand	ALDEBARAN®	
Series	GLADIUS	
Model	2K LED	
Temperature (min)	-25	°C
Temperature (max)	+40	°C
Dimensions	328 x 339 x 181	mm
Weight	7,17	kg
IP Class	IP65	
Plug	Schuko IP68 blue	
Cable Length	10	m
Feature	bolt adaption, cable reel	

Lighting Data

Attribute	Value	Unit
Luminant	2x SETO XPECT®2 LED module	
Luminous Flux	28000	lm
Luminous Flux (real)	25900	lm
Colour Temperature	4000 / 5700	K
Beam Angle	60/25	°
CRI	>70	
Durability	50000	h

Electrical Data

Attribute	Value	Unit
Input Voltage	100-240	V
Mains Frequency	50/60	Hz
Type of Current	AC	
Power Consumption	160	W
Protection Class	I	

Additional Product Images



Subject to technical changes, price adjustments and errors.

Setolite Lichttechnik GmbH Bockhackerstr. 13 42499 Hückeswagen Germany	Tel./Fax +49 2192 / 93624-0 +49 2192 / 93624-25	Web/Email www.setolite.com info@setolite.de
--	--	--

