



ALDEBARAN® XLD Compact 24 V SET

Aldebaran XLD

Article No.: **1410001605**

8.5

KG

IP65

IP CODE

38.500

LUMEN

35.000

REAL-LUMEN

Description

Much light and fastest build-up time are the key characteristics of the new ALDEBARAN® XLD(-C) COMPACT.

Like its big brother, the ALDEBARAN® XLD-2C, the ALDEBARAN® XLD(-C) COMPACT literally an extreme lighting tool: Extremely robust, extremely flexible and extremely bright, it can be extremely versatile and rapidly deploy mainly.

Thanks to its compact dimensions, it can be particularly efficient transport, thus contributing logistics costs to the reduction of. Here, the extremely robust housing made of an aluminum-nylon composite protects the powerful inner life not only reliable, but also ensures thanks to intelligent lightweight design for an extremely light weight. The assembly and disassembly is so fast, simple and reliable.

The new design also allows the use of an alternating bolt. Via quick can it can be used both from above and from below into the light. So lets run ALDEBARAN® XLD C COMPACT is very easy either normal or upside down - both on a stand and in the hanging operation.

Thanks to the optional segment circuit and dimming function can be adjusted to the required, the amount of light needed more accurately. *

By special Vorsteck discs ** glare values can be further reduced, the ALDEBARAN® XLD-C COMPACT which also ideal for use in confined spaces suitable.

If necessary, the light is also pivotable in any direction and at any angle. ***

Product Highlights

- Interchangeable connection cable
- Passive, wear-free cooling technology
- Optimal handling thanks to low weight and compact dimensions
- Overhead operation possible thanks to integrated interchangeable bolts
- Incl. transport bag and diffusers

Technical Specifications

General Data

Attribute	Value	Unit
Brand	ALDEBARAN®	
Series	XLD	
Model	COMPACT 24 V	
Temperature (min)	-25	°C
Temperature (max)	+40	°C
Dimensions	446 x 446 x 228	mm

Technical Specifications (cont.)

General Data

Attribute	Value	Unit
Weight	8.5	kg
IP Class	IP65	
Total Cable Length	5	m

Lighting Data

Attribute	Value	Unit
Colour Temperature	5000	K
Luminant	4x SETO XPECT®2 module	
Luminous Flux	38500	lm
Beam Angle	360/60	°
Luminous Flux (real)	35000	lm
CRI	>70	
Durability	50000	h

Electrical Data

Attribute	Value	Unit
Input Voltage	20-35	V
Type of Current	DC	
Power Consumption	250	W
Protection Class	III	

Accessories

Other

Article No.	Image	Name
1410000323		Tripod - 4.58 m
1410000324		WIND-UP CRANK TRIPOD, black, powder coated, incl. black center tube - 3,80m
1410000329		Telescope Tripod - 4.58 m
1410000345		SETO Construction site tripod - 3.8 m
1410000538		Fastening-Set for Wind-Up
1410000676		Transport Case for XLD Compact Series, plastic black
1410926021		Suspension Kit heavy duty
1410960016		Bolt receiver 30mm XLD Compact, changeable, silv. anodized

Accessories (cont.)

Other

Article No.	Image	Name
1410960017		Switchable bolt receiver for XLD compact with swivel ball, black anodized
1410960017-V		—
1410960037		DIN Bolt, d 30 x 100 mm, Al, for elevator tripod

Additional Product Images



Subject to technical changes, price adjustments and errors.