

ALDEBARAN® SMARTLINE RP110 LED BASIC



Aldebaran Smartline

Article No.: 1417141101

3,41

KG

IP54

IP CODE

6.500

REAL-LUMEN

Description

The lights of ALDEBARAN® SMART LINE SERIES convince with flexibility and efficiency. The simple, timeless design combines a modular basic design with the advantages of modern and energy-saving LED technology.

In conjunction with high-quality components such as the anodized aluminum housing, toughened front glass of PMMA and cold-resistant end caps a durable quality product is produced. Various possibilities for mounting, suspension and set-up to maximize potential for the use of SMART LINE lights.

In addition, help options such as motion detection means modernster microwave technology * and the variable 'Light on Demand' control energy saving potential significantly better use. Low weight and reduced height make it easy to logistical side of unbeatable advantages.

Product Highlights

- Anodized aluminum housing
- Impact-resistant, convex windscreen milky (PMMA)
- Homogeneous light
- Compact transport dimension
- Light weight

Technical Specifications

General Data

Attribute	Value	Unit
Brand	ALDEBARAN®	
Series	SMARTLINE	
Model	RP110 LED BASIC	
Temperature (min)	-25	°C
Temperature (max)	+50	°C
Dimensions	610 x 160 x 105	mm
Weight	3,41	kg
Front Window	PMMA (clear)	
IP Class	IP54	
Plug	Schuko IP68 green	
Socket	Schuko IP68 green	
Cable Length	5	m

Lighting Data

Attribute	Value	Unit
Luminant	LED STRIP-TECHNOLOGIE	
Luminous Flux (real)	6500	lm
Colour Temperature	4000	K
CRI	>80	
Durability	50000	h

Electrical Data

Attribute	Value	Unit
Input Voltage	100-240	V
Mains Frequency	50/60	Hz
Type of Current	AC	
Power Consumption	60	W
Protection Class	I	

Additional Product Images



Subject to technical changes, price adjustments and errors.