



## HEADLIGHT Railway

### Other Lights

Article No.: **1424000205**

**0,18**

KG

**IP54**

IP CODE

**(W) 320/162/59 / (R) 51**

REAL-LUMEN

### Description

The **\*\*SETO HEADLIGHT RAILWAY\*\*** is the ideal partner for service work on rails, trains and in track construction. The lightweight and compact housing, with firmly integrated, extra-long and adjustable headband, can be securely attached directly to the head or be adapted to helmets

The powerful main LED can be focused with one hand by means of a rotating ring and can thus emit either a wide cone of light for close range or a narrow-focus beam for longer distances. A three-stage brightness control can extend the runtime to up to ten hours. The red light function also enables clear signalling in shunting mode.

The **\*\*SETO HEADLIGHT RAILWAY\*\*** is particularly flexible in that both rechargeable batteries and batteries can be used for operation. The charge status can be checked via an integrated capacity indicator (see figure above). This ensures permanently safe operation in practically any environment.

### Product Highlights

- Battery compartment for 3x AAA or exchangeable battery system with USB-C charging port
- Charging via car also possible (12 to 24 V, with corresponding adapter)
- Three brightness levels
- Red light function
- Fresnel lens for homogeneous illumination of narrow spaces
- Lens with ring focus for spot or flood light
- Extra-long headband for helmet mounting
- Capacity indicator
- IP54

### Technical Specifications

#### General Data

| Attribute         | Value                     | Unit |
|-------------------|---------------------------|------|
| Series            | HEADLIGHT                 |      |
| Model             | Railway                   |      |
| Temperature (min) | -25                       | °C   |
| Temperature (max) | +55                       | °C   |
| Dimensions        | 64 x 50 x 37              | mm   |
| IP Class          | IP54                      |      |
| Weight            | 0,18                      | kg   |
| Light Functions   | (White) 100%/50%/15%; Red |      |

Lighting Data

| Attribute            | Value                   | Unit |
|----------------------|-------------------------|------|
| Luminant             | CREE XPG3               |      |
| Luminous Flux (real) | (W) 320/162/59 / (R) 51 | lm   |
| Colour Temperature   | 6500                    | K    |
| Durability           | 50000                   | h    |

Electrical Data

| Attribute                   | Value                          | Unit |
|-----------------------------|--------------------------------|------|
| Operating Time (High Level) | 6                              | h    |
| Operating Time (Low Level)  | 10                             | h    |
| Charge Time                 | 3                              | h    |
| Battery                     | 3 x AAA or Li-Po 1000mAh (USB) |      |

Additional Product Images



Subject to technical changes, price adjustments and errors.