



SETO E-POWER MOBILITY PACK EP2000

E-POWER

Article No.: 1428001020

15,5

KG

IP54

IP CODE

Description

The SETO E-POWER PACK MOBILITY is a mobile power source. Fully self-employed, the SETO E-POWER MOBILITY PACK feature select models across different capacities and thus always provide enough power for any application.

Using the supplied charger is the SETO E-POWER MOBILITY PACK recharged to its full capacity within 8 hours. Compact size and light weight make the power SETO E-POWER MOBILITY PACK ideal and indispensable companion for mobile use.

SETO E-POWER MOBILITY PACK are available in different capacities.

Product Highlights

- Integrated charge level display in %
- Impact-resistant trolley case with a trolley handle
- AC / DC outputs for various devices

Technical Specifications

General Data

Attribute	Value	Unit
Brand	SETO	
Series	E-POWER MOBILITY PACK	
Model	EP2000	
Protection	Overcharge, Overdischarge, Overload, Temperature	
IP Class	IP54	
Dimensions	408 x 311 x 166	mm
Weight	15,5	kg

Electrical Data

Attribute	Value	Unit
Input Voltage	100-240	V
Mains Frequency	50/60	Hz
Type of Current	AC	

Technical Specifications (cont.)

Electrical Data

Attribute	Value	Unit
Protection Class	II	
Output Voltage AC	220-240	V
Frequency	50	Hz
Signalform	pure sinus wave	
Power (Rated)	1400	VA
Power (Peak)	2800	VA
Output DC	5V / 2A	
Battery Type	Li-Ion	
Battery Voltage	48	V
Battery Capacity	2000	Wh
Charging Time	8	h

Accessories

Other

Article No.	Image	Name
1410950051		—

Additional Product Images



Setolite Lichttechnik GmbH
Bockhackerstr. 13
42499 Hückeswagen
Germany

Tel./Fax
+49 2192 / 93624-0
+49 2192 / 93624-25

Web/Email
www.setolite.com
info@setolite.de



Subject to technical changes, price adjustments and errors.