

## ALDEBARAN® 5000 TUBE LED

### Aldebaran 5000

Article No.: 1450800127

1,4

KG

IP65

IP CODE

1.840

REAL-LUMEN



### Description

The lamp lights even there, where others do not may only through.

The ALDEBARAN® 5000 TUBE is designed for the application in which it comes to reliable operation in adverse environments. So it is suitable for example for use in decontamination tents or bathrooms but also for any other case, is necessary in the high resistance. The consistent use of extremely resilient components made of high-performance plastics allows her to donate sustainably safe light in the toughest conditions.

### Product Highlights

- Extremely robust construction, large rubber end caps protect against impact
- Easy to clean, suitable for decontamination tents
- Cable H07BQ-F 3G1.5 mm<sup>2</sup> with plug Schuko 16 A / 230 V IP68
- Socket Schuko 16 A / 230 V IP68 opposite the feeding line

### Technical Specifications

#### General Data

| Attribute         | Value                         | Unit |
|-------------------|-------------------------------|------|
| Brand             | ALDEBARAN®                    |      |
| Series            | 5000                          |      |
| Model             | TUBE LED                      |      |
| Temperature (min) | -30                           | °C   |
| Temperature (max) | +40                           | °C   |
| Dimensions        | 120 x 800                     | mm   |
| Weight            | 1,4                           | kg   |
| IP Class          | IP65                          |      |
| Tube              | Polycarbonate clear, 60 mm    |      |
| Cable             | H07BQ-F 3G1,5 mm <sup>2</sup> |      |
| Plug              | Schuko 16 A / 230 V IP68      |      |
| Socket            | Schuko 16 A / 230 V IP68      |      |
| Cable Length      | 5                             | m    |

#### Lighting Data

| Attribute | Value             | Unit |
|-----------|-------------------|------|
| Luminant  | LED PLL TUBE 22 W |      |

# Technical Specifications (cont.)

## Lighting Data

| Attribute            | Value     | Unit |
|----------------------|-----------|------|
| Luminous Flux (real) | 1840      | lm   |
| Colour Temperature   | 4000-4500 | K    |
| CRI                  | >80       |      |
| Durability           | 50000     | h    |

## Electrical Data

| Attribute         | Value | Unit |
|-------------------|-------|------|
| Input Voltage     | 230   | V    |
| Mains Frequency   | 50    | Hz   |
| Type of Current   | AC    |      |
| Power Consumption | 22    | W    |
| Protection Class  | II    |      |

# Additional Product Images



Subject to technical changes, price adjustments and errors.