

ALDEBARAN® 5000 TUBE LED

Aldebaran 5000

Article No.: **1450800127G****1,4**

KG

IP65

IP CODE

1.840

REAL-LUMEN



Description

The lamp lights even there, where others do not may only through.

The ALDEBARAN® 5000 TUBE is designed for the application in which it comes to reliable operation in adverse environments. So it is suitable for example for use in decontamination tents or bathrooms but also for any other case, is necessary in the high resistance. The consistent use of extremely resilient components made of high-performance plastics allows her to donate sustainably safe light in the toughest conditions.

Product Highlights

- Extremely robust construction, large rubber end caps protect against impact
- Easy to clean, suitable for decontamination tents
- Cable H07BQ-F 3G1.5 mm² with plug Schuko 16 A / 230 V IP68
- Socket Schuko 16 A / 230 V IP68 opposite the feeding line
- Incl. Nylon straps (2 pieces) 1.2 m (captive)

Technical Specifications

General Data

Attribute	Value	Unit
Brand	ALDEBARAN®	
Series	5000	
Model	TUBE LED	
Temperature (min)	-30	°C
Temperature (max)	+40	°C
Dimensions	120 x 800	mm
Weight	1,4	kg
IP Class	IP65	
Tube	Polycarbonate clear, 60 mm, wall thickness 3 mm	
Cable	H07BQ-F 3G1,5 mm ²	
Plug	Schuko 16 A / 230 V IP68	
Socket	Schuko 16 A / 230 V IP68	
Cable Length	5	m

Lighting Data

Attribute	Value	Unit
Luminant	LED PLL TUBE 22 W	
Luminous Flux (real)	1840	lm
Colour Temperature	4000-4500	K
CRI	>80	
Durability	50000	h

Electrical Data

Attribute	Value	Unit
Input Voltage	230	V
Mains Frequency	50	Hz
Type of Current	AC	
Power Consumption	22	W
Protection Class	II	

Additional Product Images



Subject to technical changes, price adjustments and errors.

