



Handlamp LED IL6400 with glass lens

Atexor products

Article No.: 40__113423

1,59

KG

IP 67

IP CODE

760 / 177 / Boost 1580

REAL-LUMEN

Description

The new rechargeable IL6400 shares many of the great features of the completely plastic IL640. The addition of an aluminum clamping ring provides even better cooling. This is extremely handy when you activate function boost the by pressing the power button: Boost mode provides almost 1200 lumens ready. The IL6400 uses four high-power LEDs with a lifetime of 50,000 hours. That means you can say goodbye to the changing of the bulbs. When the battery level is low, the light in 15-second intervals starts flashing.

MICA is a guarantee for high quality, reliability and ease of use. And it shows one more time in the IL6400.

Product Highlights

- Rechargeable, environmentally friendly NIMH battery
- Useable as a signal light
- Robust splash-proof housing
- TÜV certified

Technical Specifications

General Data

Attribute	Value	Unit
Brand	MICA	
Model	IL-6400 NiMH	
Housing	Plastic PA6.6	
Temperature (min)	-20	°C
Temperature (max)	+40	°C
Dimensions	215 x 120 x 125	mm
Weight	1,59	kg
IP Class	IP 67	
Light Functions	high / low / boost	

Lighting Data

Attribute	Value	Unit
Luminant	4x CREE LED	
Luminous Flux (real)	760 / 177 / Boost 1580	lm

Electrical Data

Attribute	Value	Unit
Type of Battery	NiMH	
Battery Voltage	6	V
Operating Time (High Level)	5	h
Operating Time (Low Level)	24	h
Charge Time	11	h

Accessories

Other

Article No.	Image	Name
40__000950		H0113_1 Carrying strap (black/red) for IL600/IL6000
40__001112		Cigarette lighter cable IL-4, 3m
40__001113		Supply cable for car charging 12-30V DC, 3m
40__112300		Battery charger ILC 4, 12 - 24 V
40__112305		Charging station 5-fold Type ILC-5 for IL 640 / 6400
40__112306		Charger ILC 3-fold station
40__112700		IL-2 - 230 V

Setolite Lichttechnik GmbH
Bockhackerstr. 13
42499 Hückeswagen
Germany

Tel./Fax
+49 2192 / 93624-0
+49 2192 / 93624-25

Web/Email
www.setolite.com
info@setolite.de

