



ATEXOR MICA Handlamp ML 601-DB 1W LED w. NiMH rechargeable battery

Atexor products

Article No.: 40__114471

0,28

KG

IP54

IP CODE

40,5

REAL-LUMEN

Description

The Atexor Mica ML601 is a rechargeable, compact and powerful LED hand lamp which is designed for use in professional environments and under extreme conditions. In the ML601 LED flashlight is a special version which is additionally equipped with 2x 6 red LEDs. This means it can also be used as a signal lamp.

The casing is made of high quality, schlagresistentem nylon and the lens of tempered glass. The ML601 is splash-proof and can therefore be used for various applications. Its users include sometimes Railways and transport companies, police and border and the industrial sector.

This particularly mechanically and technically high quality battery LED hand lamp is characterized by the ease of use and durability for daily use. In addition, the lamp has an emergency light (in the charger plugged in the lamp during a power failure).

For use while a NiMH (nickel metal hydride) battery, which is valid at the time as an environment-friendly battery type. A further advantage in NiMH batteries is also that, compared with lead batteries a higher capacity is achieved for the same size; Memory effects are avoided. The user is informed by a capacity indicator on to available (residual) energy.

Generally Mica products are fully repairable and easy to maintain. Batteries can be replaced easily.

Product Highlights

- Rechargeable, environmentally friendly NIMH battery
- Useable as a signal light
- Robust, splash-proof housing
- TÜV certified

Technical Specifications

General Data

Attribute	Value	Unit
Series	ML	
Model	601	
Temperature (min)	-20	°C
Temperature (max)	+45	°C
Dimensions	120 x 64 x 55	mm

Technical Specifications (cont.)

General Data

Attribute	Value	Unit
Weight	0,28	kg
IP Class	IP54	
Light Functions	white workinglight / red signallight	

Lighting Data

Attribute	Value	Unit
Luminant	LED	
Luminous Flux (real)	40,5	lm

Electrical Data

Attribute	Value	Unit
Type of Battery	NiMH	
Battery Voltage	6	V
Operating Time (High Level)	6	h
Charge Time	max. 3	h

Accessories

Other

Article No.	Image	Name
40__001039		Part v.H0080_1, Hand strap f. ML 600/601
40__001112		Cigarette lighter cable IL-4, 3m
40__001113		Supply cable for car charging 12-30V DC, 3m
40__112700		IL-2 - 230 V
40__114453		Charging station 5-fold type MLC-5 for ML 600/601/800
40__114458		Charging station 3-fold (MLC)
40__114480		Quick battery charger MLC 12-30 V DC

Additional Product Images



Setolite Lichttechnik GmbH
Bockhackerstr. 13
42499 Hückeswagen
Germany

Tel./Fax
+49 2192 / 93624-0
+49 2192 / 93624-25

Web/Email
www.setolite.com
info@setolite.de

