



Quick battery charger MLC 12-30 V DC

Atexor products

Article No.: 40__114480

0,19

KG

Description

The terminal voltage of the charger is 12 ... 24 V / DC, and is thus provided for the car load. You must have the 3m cigarette lighter cable (Item number: 40__001112) or alternatively the supply cable with open ends (SKU 40__001113). Would you like to operate the charger to the house mains (230V), so you also need dasNetzteil IL2.

Technical Specifications

General Data

Attribute	Value	Unit
Series	ML	
Model	MLC	
Housing	Plastic	
Temperature (min)	+5	°C
Temperature (max)	+40	°C
Dimensions	142 x 83 x 22	mm
Weight	0,19	kg

Electrical Data

Attribute	Value	Unit
Charge Time	2,5	h

Accessories

Other

Article No.	Image	Name
40__001112		Cigarette lighter cable IL-4, 3m
40__001113		Supply cable for car charging 12-30V DC, 3m

Accessories (cont.)

Other

Article No.	Image	Name
40__112700		IL-2 - 230 V

Additional Product Images



Setolite Lichttechnik GmbH
Bockhackerstr. 13
42499 Hückeswagen
Germany

Tel./Fax
+49 2192 / 93624-0
+49 2192 / 93624-25

Web/Email
www.setolite.com
info@setolite.de

