



SETO LED DOUBLE-SNAKE

Path, stair and ceiling lighting for greater safety

With the **SETO LED DOUBLE-SNAKE**, a new generation of quickly installable work and safety lighting is launched. As with the SETO LED SNAKE, the **DOUBLE-SNAKE** can also be conveniently, quickly and easily unwound from a roll and installed. Installation is as simple as possible with cable ties or loop dowels.

The high IP67 protection rating of the rope (converter IP65, connector IP44) enables use in damp and dirty environments. The flexible and at the same time extremely tough rope can also be laid around corners and is at the same time extremely resistant to mechanical influences.

The highlight of the **DOUBLE-SNAKE** is that the rope light is equipped on both sides with 180 LEDs per metre and per side! This means that the rope light shines on both sides and is predestined for use in stairwells or lift shafts. Alternatively, it can also be used in corridors or tunnels without much effort.

PRODUCT FEATURES

- Extremely bright
- Highly robust and flexible
- Various mounting accessories available
- Suitable for outdoor applications

OPTIONAL ACCESSORIES

- | | |
|---|----------------------------|
| SETO LED SNAKE connecting cable "angular" 1.5 m + connector | Item no. 1428003020 |
| Clips (screwable) | Item no. 1428003021 |
| T-connector | Item no. 1428003022 |
| End cap | Item no. 1428003023 |
| Hose connector | Item no. 1428003024 |
| SETO LED SNAKE connection cable standard | Item no. 1428003028 |
| T-connector with round connection | Item no. 1428003031 |

TECHNICAL DATA

Electrical data	SETO LED DOUBLE-SNAKE 15/200	SETO LED DOUBLE-SNAKE 25/350	SETO LED DOUBLE-SNAKE 50/675
Input voltage	230 V AC, 50 Hz		
Power consumption	200 W	340 W	675 W
Lighting data			
Luminant	High-power LED, 2 x 180 pcs. per metre		
Colour temperature	5,000 K		
CRI	> 80		
General data			
IP Class	Converter IP54 / Rope IP67		
Connection	Schuko, IP44		
Operating temperature	-20 to +40 °C		
Length	15 m	25 m	50 m
Item no.	1428003005	1428003003	1428003004

